

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R31118

GRAPHITE LUBRICANT

This water base lubricant contains 22% synthetic graphite and a special high temperature additive. It is used for forging and metalworking applications at high temperatures. The 3R31118 is normally diluted with water at a varying ratio of 1:1 to 7:1 depending on the application. It is strongly recommended to preheat surfaces before application.



APPLICATIONS

This material can be used in particular for forging at high temperatures for aluminum, brass and copper extrusion. It is also recommended for the casting of billets, the coating of the ingot molds, and as a lubricant for die casting dies.

SPECIFICATIONS

Technical Data

Composition	Synthetic graphite
% of solid	22%
Particle Size	1.5 microns
Carrier	Water
рН	10
Consistency	Creamy fluid
Shelf Life	1 year under original seal

N.B. The information, details and values indicated are to the best of our know ledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.