

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0

Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R815 RUBBER

This premium quality neoprene rubber offers a moderate protection against oil, ozone and ultraviolet, and has a good impermeability to gas. It is available in three different hardness.



APPLICATIONS

The 3R815 is commonly used as flange gasketing and as static joints. It is also used in applications where the material is in contact with harsh atmospheric conditions.

SPECIFICATIONS

Technical Data

Polymer Type	Neoprene CR/SBR/NBR
Color	Black
Hardness (Shore A) ± 5	60
Temperature	-25°C to 85°C (-10°F to 185°F)
Tensile Strength, lbs/in²	1000
Elongation Minimum, %	300
Compression Set	Good
Abrasion Resistance	Very Good
Tear Resistance	Good
Ozone Resistance	Fair
Impermeability to Gases	Good
Resistance to Dilute Acid	Good
Resistance to aromatic hydro-carbons	Fair
Heat Aging	Good

N.B. The information, details and values indicated are to the best of our know ledge. We recommend to conduct tests according to local conditions. The data is subject to some variations w ithout notice.