

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R820

RUBBER

The 3R820 red rubber is made of a commercial blend of Styrene-Butadiene (SBR). It is also available in a red smooth finish.



APPLICATIONS

It is commonly used as domestic and commercial gaskets for air, hot and cold water and low pressure steam.

SPECIFICATIONS

Technical Data

Polymer Type	Red Rubber SBR
Color	Red
Hardness (Shore A) ± 5	75
Temperature	-25°C to 80°C (-10°F to 180°F)
Tensile Strength, Ibs/in²	600
Elongation minimum, %	100
Compression Set	Good
Abrasion Resistance	Good
Tear Resistance	Fair
Ozone Resistance	Poor
Impermeability to Gases	Poor
Resistance to Dilute Acid	Fair
Resistance to aromatic hydro-carbons	Poor
Heat Aging	Fair

N.B. The information, details and data is subject to some variation	d values indicated are to the ns w ithout notice.	best of our know ledge.	We recommend to conduct	tests according to local conditions	. The