

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R826

RUBBER

A general purpose SBR rubber that offers good abrasion resistance and tensile strength at an economical price. It is available in four different hardness.



APPLICATIONS

The 3R826 is used for various gasketing and skirtboard applications.

SPECIFICATIONS

Technical Data

Polymer Type	Rubber SBR
Color	Black
Hardness (Shore A) ± 5	60
Temperature	-25°C to 80°C (-10°F to 180°F)
Tensile Strength, lbs/in²	500
Elongation minimum, %	300
Compression Set	Good
Abrasion Resistance	Good
Tear Resistance	Fair
Ozone Resistance	Poor
Impermeability to Gases	Poor
Resistance to Dilute Acid	Fair
Resistance to aromatic hydro-carbons	Poor
Heat Aging	Fair

N.B. The information, details and data is subject to some variation	d values indicated are to the ns w ithout notice.	best of our know ledge.	We recommend to conduct	tests according to local conditions	. The