



industries3r.com

Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

GRA2550 /GRA2551

GRAPHITE TAPE

The GRA2250 is made from high purity graphite with no fibers, binders or other additives. It is identical to the GRA2550 but has an adhesive tape. This tape be used to seal multiple shapes and irregular surfaces.



APPLICATIONS

This graphite tape covers a broad range of sealing applications. It handles most chemicals in the 0 - 14 pH range, elevated temperatures from -320 °F to 5400 °F. It is used extensively in the chemical, automotive and pump and valve industries.

SPECIFICATIONS

Service limits

Temperature limits	
Minimum	-200°C (-325°F)
Maximum in air	450°C (840°F)
In steam	645°C (1190°F)
In reducing or inert media	3000°C (5400°F)
Pressure: Static	2000 psi (137 bar)
pH	0-14

N.B. The information, details and values indicated are to the best of our know ledge. We recommend to conduct tests according to local conditions. The data is subject to some variations w ithout notice.