



industries3r.com

Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

TACKY M

RUBBER COATED FIBERGLASS

The Tacky M is a fiberglass fabric with a brass wire insertion and is impregnated with a natural rubber solution. This coating resists to high temperatures and increases the pressure resistance of the fabric.



APPLICATIONS

This fabric is currently used in the fabrication of handhole and manhole gaskets and sealing tapes.

SPECIFICATIONS

Technical Data

Thickness	1/16", 1/8", 3/16", 1/4"
Width	40"
Max. Temperature	200°C (390°F)
Max. Pressure	180 psi
Resistance	Steam, water, mild alkalis and acids
Weight (oz/yd²)	64

N.B. The information, details and values indicated are to the best of our knowledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.