



INDUSTRIES 3R

# SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION

### IDENTITY:

Part Number:

**TXP 176**

Identity:

Colored woven fiberglass cloth

Description:

Continuous filament fibreglass

### SUPPLIER :

**Industries 3R Inc.**

55, route 116 Ouest

Danville (Québec) J0A 1A0

Tel: 819-839-2793

Fax: 819-839-2797

## SECTION 2. HAZARDS IDENTIFICATION



### WARNING

#### Precautionary Statements:

P281: Wear personal protective equipment as required

P302: If on skin, wash with mild soap and running water

P304: If inhaled, move individual to fresh air. Seek medical attention if irritation persists

P305: If in eyes, flush eyes at least 15 minutes; seek medical attention if irritation persists

#### Hazard Statements: N/A

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Abstracts Service Number: 65997-17-3 (Fiberglass)

<u>Hazardous Ingredients</u>	<u>Weight %</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>OTHER</u>
Fiberglass, continuous Filament	≥ 96.5	a.	5 mg/ m <sup>3</sup> .8 hr TWA (inhalable) 1 fiber/cm <sup>3</sup> 8-hr TWA (respirable)	3 x 10 <sup>6</sup> fibers/m <sup>3</sup> 10-hr TWA (NIOSH)
<u>Nonhazardous Ingredients</u>				
Sizing	≤ 3.5	-----none established-----		

- a. OSHA has not established a specific PEL for fibrous glass. It is considered to be a "particulate not otherwise regulated" (PNOR) and is covered under the OSHA nuisance dust PEL's of 5 mg/m<sup>3</sup> for the respirable dust fraction and 15 mg/m<sup>3</sup> for the total dust fraction for an 8-hr TWA (Time Weighted Average).

#### **SECTION 4. FIRST AID MEASURES**

- Inhalation:** Move individual to fresh air. Seek medical attention if irritation persists.
- Skin Contact:** Wash with mild soap and running water. Use a washcloth to help remove fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical attention if irritation persists.
- Eye Contact:** Flush eyes with flowing water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** N/A. (Not Applicable)

#### **SECTION 5. FIRE FIGHTING MEASURES**

- Extinguishing Equipment:** water, foam, carbon dioxide, dry chemical
- Special Fire-Fighting Instructions:** In a sustained fire, self contained breathing apparatus should be worn.
- Unusual Fire and Explosion Hazards:** None known.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

- ACTION TO TAKE FOR SPILLS ( Use Appropriate Safety Equipment/PPE):**  
For solid product, not applicable.  
For dusts and fibers generated during fabrication, vacuum and containerize.

#### **SECTION 7. HANDLING AND STORAGE**

- Handling:** See Section 8.
- Storage:** No special precautions necessary.
- Disposal:** Dispose in accordance with federal, state and local regulations as a solid nonhazardous waste.

#### **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Ventilation:** General dilution ventilation and/or local exhaust ventilation should be provided, as necessary, to maintain exposures below PEL's or TLV's. **Adequate ventilation must be provided at elevated temperatures.**
- Respiratory Protection:** A properly fitted NIOSH/MHSA approved disposable dust respirator such as the 3M model 8210 or model 9900 (in high humidity environments) or equivalent should be used when: high dust levels are encountered; the level of glass fibers in the air exceeds the OSHA permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulations under 29 CFR 1910.134.
- Eye Protection:** Safety glasses, goggles or face shields should be worn whenever fiberglass materials are being handled.

Protective Clothing: Wear loose fitting, long sleeved shirt that covers to the base of the neck, and long pants. Skin irritation from exposure to fiberglass is known to occur chiefly at pressure points such as around the neck, wrist and waist. Wear gloves when handling product.

Work/Hygienic Practices: Handle in accordance with good industrial hygiene and safety practices:

- = Avoid unnecessary exposure to dusts and fibers
- = Remove fibers from skin after exposure
- = Be careful not to rub or scratch irritated areas. Rubbing or scratching may force the fibers into the skin. The fibers should be washed off. Use of barrier creams can, in some instances, be helpful.
- = Use vacuum equipment to remove fibers and dusts from clothing. **COMPRESSED AIR SHOULD NEVER BE USED**. Always wash work clothes separately and wipe out the washer/sink in order to prevent loose glass fibers from getting on other clothes.
- = Keep the work area clean of any dusts and fibers generated during fabrication. Use vacuum equipment to clean up dusts and fibers. Avoid sweeping or using compressed air as these techniques resuspend dusts and fibers into the air.
- = Have access to safety showers and eye wash fountains.
- = For professional use only. **Keep out of children's reach.**

Exposure Limits (TLVS): N/A

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point (Softening): 800°C      Boiling Point(°C): N/A (Not Applicable)

Specific Gravity (Bare Glass): 2.59      Percent Volatile: N/A

Vapor Pressure: (mm Hg): N/A      Vapor Density (Air = 1): N/A

Evaporative Rate (Ethyl Ether = 1): N/A      Solubility in Water: Not soluble

Appearance and Odor: White/off-white/tan colored solid with no odor.

pH: N/A      Relative Density: N/A

Upper/Lower Flammability or Exposure Limits: N/A

Freezing Point: N/A      Flash Point: N/A

Partition coefficient (n-octanol/water): N/A      Auto Ignition Temperature: N/A

Decomposition Temperature: N/A      Viscosity: N/A

## **SECTION 10. STABILITY AND REACTIVITY**

Stability (Conditions to Avoid): Product is stable.

Stabilizers: N/A

Incompatibility (Materials to Avoid): None known.

Hazardous Decomposition Products: Sizings or binders may decompose in a fire. Primary decomposition products include carbon monoxide, carbon dioxide, other hydrocarbons and water.

Hazardous Polymerization: Will not occur.

Flash Point (°F): N/A (Not Applicable)

Auto Ignition Temperature (°F): N/A

Flammability Limits (%): LEL: N/A UEL: N/A

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Primary Routes of Exposure: Inhalation and skin contact.

Health Hazards (Including acute and chronic effects and symptoms of overexposure):

<u>ACUTE:</u>	<u>Inhalation:</u>	Inhalation of dusts and fibers may result in irritation of the upper respiratory tract (mouth, nose and throat)
	<u>Skin Contact:</u>	Skin contact with dusts and fibers may produce itching and temporary mechanical irritation.
	<u>Eye Contact:</u>	Eye contact with fibers and dusts may produce temporary mechanical irritation.
	<u>Ingestion:</u>	Temporary mechanical irritation of the digestive tract. Observe individual. If symptoms develop, consult a physician.
<u>CHRONIC:</u>		See carcinogenicity section below. There are no known health effects associated with chronic exposure to this product.

