



INDUSTRIES 3R

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

IDENTITY:

Part Number: **TXP 404**
 Identity: Woven fiberglass coated with silicone elastomer
 Description: Continuous filament fiberglass coated with compounded polysiloxane polymer

SUPPLIER :

Industries 3R Inc.
 55, route 116 Ouest
 Danville (Québec) J0A 1A0
 Tel: 819-839-2793
 Fax: 819-839-2797

Recommended use of the product: data not available

SECTION 2. HAZARDS IDENTIFICATION



WARNING

Precautionary Statements:

P281: Wear personal protective equipment as required
 P302: If on skin, wash with mild soap and running water
 P304: If inhaled, move individual to fresh air. Seek medical attention if irritation persists
 P305: If in eyes, flush eyes at least 15 minutes; seek medical attention if irritation persists

Hazard Statements: N/A

Chemical Abstracts Service Number: 65997-17-3 (Fiberglass)

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Hazardous Ingredients</u>	<u>Weight%</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>OTHER</u>
Fiberglass, continuous filament	≥ 66.5 to ≥ 81.5	a.	5 mg/ m ³ 8-hr TWA	3 x 10 ⁶ fibers/m ³ 10-hr TWA (NIOSH)
Compounded polysiloxane Polymer	15.0 to 30.0	-----	Not know	-----

Nonhazardous Ingredients

Sizing ≤ 3.5 -----none established-----

OSHA has not established a specific PEL for fibrous glass. It is considered to be a “particulate not otherwise regulated” (PNOR) and is covered under the OSHA nuisance dust PEL’s of $5\text{mg}/\text{m}^3$ for the total dust fraction for an 8-hour TWA (Time Wighted Average).

SECTION 4. FIRST AID MEASURES

Inhalation: Move individual to fresh air. Seek medical attention if irritation persists.
Skin Contact: Wash with mild soap and running water. Use a washcloth to help remove fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical attention if irritation persists.
Eye Contact: Flush eyes with flowing water for at least 15 minutes. Seek medical attention if irritation persists.
Ingestion: N/A (Not Applicable)

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing Equipment: water, foam, carbon dioxide, dry chemical
Special Fire-Fighting Instructions: In a sustained fire, self contained breathing apparatus should be worn.
Unusual Fire and Explosion Hazards: None known.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Action To Take For Spills (Use Appropriate Safety Equipment/PPE):
For solid product, not applicable.
For dusts and fibers generated during fabrication, vacuum and containerize.

SECTION 7. HANDLING AND STORAGE

Handling: See Section 8.
Storage: No special precautions necessary.
Disposal: Dispose in accordance with federal, state and local regulations as a solid nonhazardous waste.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: General dilution ventilation and/or local exhaust ventilation should be provided, as necessary, to maintain exposures below PEL's or TLV's. **Adequate ventilation must be provided at elevated temperatures.**
Respiratory Protection: A properly fitted NIOSH/MHSA approved disposable dust respirator such as the 3M model 8210 or model 9900 (in high humidity environments) or equivalent should be used when: high dust levels are encountered; the level of

	glass fibers in the air exceeds the OSHA permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulations under 29 CFR 1910.134.
<u>Eye Protection:</u>	Safety glasses, goggles or face shields should be worn whenever fiberglass materials are being handled.
<u>Protective Clothing:</u>	Wear loose fitting, long sleeved shirt that covers to the base of the neck, and long pants. Skin irritation from exposure to fiberglass is known to occur chiefly at pressure points such as around the neck, wrist and waist. Wear gloves when handling product.
<u>Work/Hygienic Practices:</u>	Handle in accordance with good industrial hygiene and safety practices: <ul style="list-style-type: none"> - Avoid unnecessary exposure to dusts and fibers - Remove fibers from skin after exposure - Be careful not to rub or scratch irritated areas. Rubbing or scratching may force the fibers into the skin. The fibers should be washed off. Use of barrier creams can, in some instances, be helpful. - Use vacuum equipment to remove fibers and dusts from clothing. COMPRESSED AIR SHOULD NEVER BE USED. Always wash work clothes separately and wipe out the washer/sink in order to prevent loose glass fibers from getting on other clothes. - Keep the work area clean of any dusts and fibers generated during fabrication. Use vacuum equipment to clean up dusts and fibers. Avoid sweeping or using compressed air as these techniques resuspend dusts and fibers into the air. - Have access to safety showers and eye wash fountains. - For professional use only. Keep out of children's reach.
<u>Exposure Limits (TLVS):</u>	N/A

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point (Softening):	N/M (Not Measured)
Boiling Point (°C):	N/A (Not Applicable)
Specific Gravity (Bare Glass):	N/M
Percent Volatile:	N/A
Vapor Pressure (mm Hg):	N/A
Vapor Density (Air=1):	N/A
Evaporative Rate (Ethyl Ether=1):	N/A
Solubility in water:	Not soluble
Appearance and odor:	Flexible coated fabric of various colors with no odor.
pH:	N/A
Relative Density:	N/A
Upper/Lower Flammability or Exposure Limits:	N/A
Freezing Point:	N/A
Flash Point:	N/A
Partition coefficient (n-octanol/water):	N/A

Auto Ignition Temperature: N/A
Decomposition Temperature: N/A
Viscosity: N/A

SECTION 10. STABILITY AND REACTIVITY

Stability (Conditions to Avoid): Product is stable
Stabilizers: N/A
Incompatibility (Materials to Avoid): None known.
Hazardous Decomposition Products: Sizings or binders may decompose in a fire. Primary decomposition products include carbon monoxide, carbon dioxide, other hydrocarbons and water.
Hazardous Polymerization: Will not occur.
Flash Point (oF): N/A (Not Applicable)
Auto Ignition Temperature (oF): N/A
Flammability Limits (%): LEL: N/A UEL: N/A

SECTION 11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation and skin contact.

Health Hazards (Including acute and chronic effects and symptoms of overexposure):

Acute:

Inhalation: Inhalation of dusts and fibers may result in irritation of the upper respiratory tract (mouth, nose and throat).

Skin Contact: Skin contact with dusts and fibers may produce itching and temporary mechanical irritation.

Eye Contact: Eye contact with fibers and dusts may produce temporary mechanical irritation.

Ingestion: Temporary mechanical irritation of the digestive tract. Observe individual. If symptoms develop, consult a physician.

Chronic: See carcinogenicity section below. There are no known health effects associated with chronic exposure to this product.

Carcinogenicity:

Hazardous Ingredients:	Listed as carcinogen by:	<u>ACGIH</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
Fiberglass continuous filament		No	No*	No	No
Compounded polysiloxane polymer		-----Not Known-----			

*IARC: In June, 1987 the International Agency for Research on Cancer (IARC) categorized fibreglass continuous filaments as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify fibreglass continuous filaments as a possible, probable, or confirmed cancer causing material.

Medical Conditions Aggravated by Exposure:

Persons with a history of chronic respiratory or skin conditions that are aggravated by mechanical irritants may be at increased risk for worsening their condition from exposure during use of the product.

SECTION 12. ECOLOGICAL INFORMATION

N/A

SECTION 13. DISPOSAL CONSIDERATIONS

See Section 8 (if applicable)

SECTION 14. TRANSPORT INFORMATION

N/A

SECTION 15. REGULATORY INFORMATION

N/A

SECTION 16. OTHER INFORMATION

DISCLAIMER – The information provided in this Safety Data Sheet is based on the data furnished by our suppliers. While the information and recommendations set forth herein are believed to be accurate, Industries 3R takes no warranty with respect thereto and disclaims all liability in reliance thereon. We recommend testing according to local conditions. The specifications are subject to change without notice.

Last update: December 5th, 2018