



industries3r.com

Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

TXP405

SILICONE COATED FIBERGLASS

The TXP405 is a satin weaved fiberglass fabric coated with a silver rubberized silicone. It resists abrasion, flexing, tearing and puncturing. It protects from water, oil and chemical products and generates little smoke.



APPLICATIONS

This fabric is used for removable blankets, expansion joints, welding curtains and flexible connectors.

SPECIFICATIONS

Technical Data

Temperature	-50°C to 260°C (-55°F to 500°F)
Color	Grey
Weight	32oz/yd²
Thickness	0.035"
Flame Resistance	Flame out (sec) 1 sec. Max. Afterglow (sec) 1 sec. Max. Char length (in) 1/16" max.
Tensile strength	Wrap 500 lbs/in minimum average Fill 400 lbs/in minimum average
Tear Strength	Wrap 75 lbs minimum average Fill 40 lbs minimum average
Mullen Burst	400 psi minimum average
Certifications	NFPA701/1999, ANSI/FM4950 for hot work protection

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.