



industries3r.com

**Danville office**

Industries 3R inc.  
55, Road 116 West  
Danville (Quebec)  
Canada J0A 1A0

Telephone: (819) 839-2793  
Fax: (819) 839-2797  
Toll-free: (800) 567-2728  
Email: info@industries3r.com

**Montreal office**

Industries 3R inc.  
1479, Begin street  
Ville St-Laurent (Quebec)  
Canada H4R 1V8

Telephone: (514) 333-3971  
Fax: (514) 333-7224  
Email: info@industries3r.com

# TXP405

## SILICONE COATED FIBERGLASS

The TXP 405 is a satin weaved fiberglass fabric coated with a silver rubberized silicone. It resists to temperatures up to 500°F, abrasion, flexing, tear and puncturing. It protects from water, oil and chemical products and generates little smoke.



### APPLICATIONS

This fabric is used for removable blankets, expansion joints, welding curtains and flexible connectors.

### SPECIFICATIONS

#### Technical Data

<b>Color-Coating</b>	<b>Grey</b>
<b>Weight (oz/yd<sup>2</sup>)</b>	<b>32</b>
<b>Thickness</b>	<b>0.035"</b>
<b>Flame Resistance</b>	<b>Flame out (sec) 1 sec. Max. Afterglow (sec) 1 sec. Max. Char length (in) 1/16" max.</b>
<b>Tensile strength</b>	<b>Wrap 500 lbs/in minimum average Fill 400 lbs/in minimum average</b>
<b>Tear Strength</b>	<b>Wrap 75 lbs minimum average Fill 40 lbs minimum average</b>
<b>Mullen Burst</b>	<b>400 psi minimum average</b>
<b>Temperature</b>	<b>-50°C to 260°C (-55°F to 500°F)</b>

**N.B.** The information, details and values indicated are to the best of our know ledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.

