

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

TXP660

FIBERGLASS

The TXP660 fiberglass tubular form sleeves are very soft and flexible. They can easily fit over uneven surfaces, bend around sharp corners and are made for high temperature industrial and commercial applications.



APPLICATIONS

The TXP660 tubinga are commonly used to insulate hot and cold pipes and for covering supports and static joints. In electrical engineering, they are used to isolate and protect the coils and conductors exposed to high temperatures or damage caused by abrasion or by stressors. They are completely non-combustible and resist to most acids and alkali.

SPECIFICATIONS

Technical Data

Temperature	535°C (1000°F)
Tensile strenght	stable up to 260°C (500°F)
Inside diameter	
1/4" to 3"	

N.B. The information, details and values indicated are to the best of our knowledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.