



industries3r.com

Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

TYPE NP1

NEOPRENE POLYESTER

Made of a lightweight polyester fabric coated with neoprene with a galvanized external helix. It resists flames and abrasions. It is flexible and exhibits excellent breaking and tear strength. It is lightweight and flexible.



APPLICATIONS

General service dust collection

SPECIFICATIONS

Technical Data

Temperature	Continuous: -40°C to 116°C (-40°F to 240°F), Short period: 135°C (275°F)
Ratio	6:1
Color	Black
Flame resistance	UL 94 V-0
Abrasion resistance	ASTM D3889 (85a)

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.