



[industries3r.com](http://industries3r.com)

**Danville office**

Industries 3R inc.  
55, Road 116 West  
Danville (Quebec)  
Canada J0A 1A0

Telephone: (819) 839-2793  
Fax: (819) 839-2797  
Toll-free: (800) 567-2728  
Email: [info@industries3r.com](mailto:info@industries3r.com)

**Montreal office**

Industries 3R inc.  
1479, Begin street  
Ville St-Laurent (Quebec)  
Canada H4R 1V8

Telephone: (514) 333-3971  
Fax: (514) 333-7224  
Email: [info@industries3r.com](mailto:info@industries3r.com)

# WR

## SPIRAL GASKETS

These gaskets are constructed with a metallic guide ring, metallic winding and a filler element. The metallic winding, of special profile, provides excellent resistance, compensating the changes in operational conditions such as variations of pressure and temperatures, vibrations, thermal shocks, etc. It acts as a spring which makes the gasket very resilient. The filler materials fill the irregularities of the flanges, assuring an airtight seal. Its external guide ring has the function of centering the gasket in the flanges and gives the sealing elements additional resistance to the flow pressure, also avoiding excessive bolt torque.



## APPLICATIONS

Temperature and pressure variations

## SPECIFICATIONS

### Technical Data

Temperature (Filler material)	<b>Flexible graphite: -212°C to 510°C (-350°F to 950°F)</b>
Temperature (metal spiral)	<b>304SS (Yellow) and 316L SS (Green): -195°C to 760°C (-320°F to 1400°F)</b>

**N.B.** The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.