

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R710

RAMIE

3R 710 packing is braided with high quality ramie yarns in a square plait construction. The yarns are heavily impregnated throughout with paraffin and mineral oil.



APPLICATIONS

This packing is a well lubricated, medium-hard packing with extremely low frictional characteristics, which assure minimal shaft wear. The ramie yarn is rot and mildew resistant, making the packing ideal for marine use, handling cold water, salt water, and cold oils. In the marine industry, it is commonly used in stern tubes, rubber posts, and tail shaft liners. This style is also used in the pulp and paper, waste/wastewater, steel and mining industries.

SPECIFICATIONS

Service limits

Maximum temperature	100°C (210°F)	
Pressure		
Rotating	217.6 psi (15 bar)	
Reciprocating	217.6 psi (15 bar)	
Static	290 psi (20 bar)	
Shaft Speed	1200 fpm (6 m/s)	
рН	6-8	

Approximate yields - Feet per pound (+/- 10%)

1/8"	114
3/16"	42.6

1/4"	33.1
5/16"	19.1
3/8"	13.5
7/16"	11
1/2"	8.1
9/16"	7.5
5/8"	4.8
3/4"	3.4
7/8"	2.9
1"	2.1
1-1/8"	1.6
1-1/4"	1.4
1-1/2"	1.0

N.B. The information, details and values indicated are to the best of our knowledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.