



industries3r.com

Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

3R720

PTFE

3R 720 packing is a firm, high density interlock braided packing manufactured from pure ePTFE filaments pretreated with PTFE dispersion, but contains no other lubricants. The PTFE dispersion provides a low friction surface finish and prevents leakage through the braid.



APPLICATIONS

This packing is especially suited for oxygen service and other services where lubricants other than PTFE cannot be tolerated. 3R720 is commonly used in valves and lower shaft speed applications. It is resistant to most chemicals, aggressive fluids, gases and solvents, with the exception of molten alkali metals.

SPECIFICATIONS

Technical Data

Temperature	-268°C to 280°C (-450°F to 539°F)
Pressure	Static: 3600 psi (250 bar), Rotating: 290 psi (20 bar), Reciprocating: 2150 psi (150 bar)
Shaft Speed	987 fpm (5 m/s)
pH	0-14

Approximate yields - Feet per pound (+/- 10%)

1/8"	94.5
3/16"	42
1/4"	21.3
5/16"	13.9
3/8"	9.9
7/16"	7.4

1/2"	5.3
9/16"	4.3
5/8"	3.6
3/4"	2.5
7/8"	1.9
1"	1.6

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.