


industries3r.com
Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

3R732 FDA

PTFE

The 3R732 packing is a firm, pliable interlock braided packing manufactured from the purest PTFE filaments. A proprietary food grade lubricant provides faster break-in and reduced shaft wear. It complies with the F.D.A. and U.S.D.A. requirements under Title 21 Food and Drugs: Part 177.1500 - Perfluorocarbon Resins and Part 178.3570 - Lubricants with Incidental Food Contact.



APPLICATIONS

This packing resists most caustic media and is commonly used in centrifugal and rotary food processing equipment. It is also used in blenders, mixers, cookers, dryers and pumps

SPECIFICATIONS

Technical Data

Temperature	-100°C to 280°C (-148°F to 536°F)
Pressure	Rotating: 290psi (20 bar), Reciprocating: 435psi (30 bar)
Shaft Speed	2350 fpm (12 m/s)

Service limits

pH	0-14
----	------

Approximate yields - Feet per pound (+/- 10%)

1/8"	79.6
3/16"	36
1/4"	20.2
5/16"	11.9

3/8"	8.4
7/16"	6.3
1/2"	5.1
9/16"	3.8
5/8"	3.2
3/4"	2.1
7/8"	1.6
1"	1.3

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.