

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R746

FLEXIBLE GRAPHITE

The 3R 746 packing is manufactured from high purity flexible graphite that is expanded and formed into a braidable yarn and then braided without binders or wire reinforcement. The finished product retains all the inherent benefits of flexible graphite: heat resistance, chemical inertness, low friction, self lubrication and ready conformability.



APPLICATIONS

This versatile packing can be used in many applications such as in valves, pumps, expansion joints, mixers and agitators in the hostile environments of hydrocarbon processing, pulp and paper, power generation, metal-working and other industries where effective sealing is vital.

SPECIFICATIONS

Service limits

Minimum temperature	-240°C (-400°F)	
Maximum temperature	450°C (840°F)	
In steam	1200°F	
Pressure		
Rotating	435 psi (30 bar)	
Reciprocating	1450 psi (100 bar)	
Static	4350 psi (300 bar)	
Shaft speed	5904 fpm (30 m/s)	
рН	0-14 (except strong oxidizers)	

Approximate yields - Feet per pound (+/- 10%)

 1/8"	112

3/16"	50
1/4"	28.5
5/16"	18.2
3/8"	13.2
7/16"	9.6
1/2"	7.4
9/16"	6.1
5/8"	4.9
3/4"	3.6
7/8"	2.6
1"	2.1

N.B. The information, details and values indicated are to the best of our knowledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.