

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

3R850

RUBBER

The 3R850 has excellent resistance to flame, heat, ozone, general chemicals, acids and alkali. This material is designated for outdoor use when a product resistant to sunlight, oxidation and ozone is needed. However, it has a low resistance to oils and solvents.



APPLICATIONS

Gaskets

SPECIFICATIONS

Technical Data

Polymer Type	Hypalon CSM
Color	Black
Hardness (Shore A) ± 5	60
Temperature	-25°C to 85°C (-13°F to 185°F)
Tensile Strength	1200lbs/in² min.
Elongation	300% min.
Compression Set	Fair
Abrasion Resistance	Very Good
Tear Resistance	Fair
Ozone Resistance	Outstanding
Impermeability to Gases	Excellent
Resistance to Dilute Acid	Excellent
Resistance to aromatic hydro-carbons	Fair
Heat Aging	Very Good

N.B. The inforesults obtain	rmation present led by the applic	ted may differ fro cation of this info	om practice. We ormation or the s	recommend co afety and suital	nducting tests a bility of our prod	according to the ducts. The data	e conditions of u is subject to ce	se. We accept rtain variations	no responsibility for without notice.