

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0

Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com



The Glassmat insulation is entirely made of fiber glass and is needled mechanically by means of a modern production method without addition of binders. This fiberglass mat is incombustible



APPLICATIONS

The Glassmat is commonly used as an insulating material in expansion joints and protective mattresses due to its excellent insulating properties and good vibration stability.

SPECIFICATIONS

Technical Data

Temperature	550°C (1020°F)
% Fiberglass fiber	98%
Thickness	1/2", 1"
Density	160 kg/m³
Thermal conductivity DIN EN 1094 (W / m / k)	
50°C	0.041
100°C	0.046
200°C	0.060
300°C	0.078
400°C	0.100
500°C	0.125

N.B. The information, details and values indicated are to the best of our know ledge. We recommend to conduct tests according to local conditions. The data is subject to some variations w ithout notice.