

### industries3r.com

### Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

#### Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

# TXP507A

# **TEFLON COATED FIBERGLASS**

The TXP507A is a medium-weight woven fiberglass fabric coated with PTFE resin on both sides. It is highly resistant to outdoor conditions, chemicals, and abrasion. It has excellent antistatic properties and outstanding chemical resistance. This fabric is rigid, non-sticky, easy to sew, and easy to clean. It is designed for sealing suspended roofs of oil tanks, sealing chemical storage tanks, dust insulation, and other types of fire control systems.



# **APPLICATIONS**

Removable insulation blankets
Protective sleeves for valves, pumps, flanges
Protection against frost
Protection against chemicals

## **SPECIFICATIONS**

## **Technical Data**

Weave	4H Satin
Construction (ASTM D 3775-96)	Warp: 48 ends/inch (18 ends/cm) Weft: 32 picks/inch (12.6 picks/cm)
Weight (ASTM D3776-96)	12.6 oz/yd² (430 g/m²)
Thickness	0.015" (0.37 mm)
coated fabric	
Coating	PTFE coated on both sides
Weight (ASTM D3776-96)	18 oz/yd² (610 g/m²)
Thickness (ASTM D1777-96)	0.017" (0.45 mm)
Color	Black
Fire resistance	Flame retardant
Antistatic	Yes (Static Dissipative)

Temp resistance	Glass fabric: Up to 1000°F (550°C) PTFE coating: Up to 620°F (330°C)

**N.B.** The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.