



[industries3r.com](http://industries3r.com)

**Danville office**

Industries 3R inc.  
55, Road 116 West  
Danville (Quebec)  
Canada J0A 1A0

Telephone: (819) 839-2793  
Fax: (819) 839-2797  
Toll-free: (800) 567-2728  
Email: [info@industries3r.com](mailto:info@industries3r.com)

**Montreal office**

Industries 3R inc.  
1479, Begin street  
Ville St-Laurent (Quebec)  
Canada H4R 1V8

Telephone: (514) 333-3971  
Fax: (514) 333-7224  
Email: [info@industries3r.com](mailto:info@industries3r.com)

# TXP527

## HYPALON

Resistant to ozone, to flex cracking, chemical products and water, this fiberglass fabric is coated with white hypalon on both sides. It is fire retardant.



## APPLICATIONS

The TXP527 is an excellent choice for the confection of bellows and flexible ducting.

## SPECIFICATIONS

### Technical Data

<b>Weight (ASTM-D-3776) (oz/y<sup>2</sup>)</b>	<b>29.5</b>
<b>Thickness (ASTM D-1777)</b>	<b>0.027"</b>
<b>Tensile strength (ASTM D-5587)</b>	
Warp	2 200 N
Fill	2 200 N
<b>Tear strength (ASTM D-5587)</b>	
Warp	170 N
Fill	170 N
<b>Temperature</b>	<b>120 °C (250 °F)</b>
<b>Flame Resistance</b>	<b>Self extinguishing</b>

**N.B.** The information, details and values indicated are to the best of our knowledge. We recommend to conduct tests according to local conditions. The data is subject to some variations without notice.

