

**industries3r.com****Danville office**

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

TYPE 1500-HT

POLYURETHANE FIBERGLASS

Two-layers fiberglass coated with polyurethane ducting with encapsulated woven fiberglass tape and a stainless steel external helix. Water repellent and flexible, it is resistant to mineral oil, abrasion, cuts and high temperatures.



APPLICATIONS

Diesel exhaust
High temperature extraction
Other vehicle applications

SPECIFICATIONS

Technical Data

Temperature	Minimum: -40°C (-40°F), Continuous: 815°C (1500°F), Short term: 885°C (1625°F)
Weight (lbs/ft)	1.56
Ratio	3:1
Color	Red

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.