

**industries3r.com****Danville office**

Industries 3R inc.  
55, Road 116 West  
Danville (Quebec)  
Canada J0A 1A0

Telephone: (819) 839-2793  
Fax: (819) 839-2797  
Toll-free: (800) 567-2728  
Email: [info@industries3r.com](mailto:info@industries3r.com)

**Montreal office**

Industries 3R inc.  
1479, Begin street  
Ville St-Laurent (Quebec)  
Canada H4R 1V8

Telephone: (514) 333-3971  
Fax: (514) 333-7224  
Email: [info@industries3r.com](mailto:info@industries3r.com)

## TYPE 900-HT

### POLYURETHANE FIBERGLASS

Fiberglass coated ducting with polyurethane and a galvanized steel external helix. Water repellent and flexible, it is resistant to mineral oils, abrasion and cuts.



## APPLICATIONS

Diesel exhaust  
High temperature extraction  
Other vehicle applications

## SPECIFICATIONS

### Technical Data

Temperature	Minimum: -30°C (-22°F), Continuous: 480°C (900°F), Courte durée: 520°C (975°F)
Weight (lbs/ft)	0.66
Ratio	4:1
Color	Red

**N.B.** The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.