

**industries3r.com****Danville office**

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

TYPE SGR

SILICONE FIBERGLASS

Ducting made of fiberglass fabric impregnated with silicone rubber with a galvanized external helix. It is considerably light weight, water and oil resistant and flame retardant. This product is extremely flexible, offers excellent abrasion resistance and is highly tear and puncture resistant.



APPLICATIONS

Fume extraction
High temperature applications

SPECIFICATIONS

Technical data

Temperature	Continuous: -55°C to 260°C (-67°F to 500°F), Short term: 371°C (700°F)
Weight (lbs/ft)	0.75
Compression ratio	6:1
Color	Red

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.